



TOPLINE LASER

	Topline Laser with Height sensor	Topline Laser with Key FOB	Topline Laser with Vibration Sensor
Dimensions, mm:	490x70x85 - class 2a; 560x70x85 - class 2b; 610x70x85 - class 3a; 705x70x85 - class 3b;	490x70x85 - class 2a; 560x70x85 - class 2b; 610x70x85 - class 3a; 705x70x85 - class 3b;	490x70x85 - class 2a; 560x70x85 - class 2b; 610x70x85 - class 3a; 705x70x85 - class 3b;
Material:	Steel/ABS covers	Steel/ABS covers	Steel/ABS covers
Colour:	yellow	yellow	yellow
Laser Power:	<5mW	<5mW	<5mW
Wave length:	520 nm	520 nm	520 nm
Power supply:	5 V/DC	5 V/DC	5 V/DC
Laser class:	3R	3R	3R
Battery version	Li-Ion	Li-Ion	Li-Ion
Battery capacity:	6,7 Ah	6,7 Ah	6,7 Ah
Batteries incl.:	2 pcs.	2 pcs.	2 pcs.
Charger power:	8,4 V/DC	8,4 V/DC	8,4 V/DC
Activation by:	Height	Remote control	Vibration
Laser colour:	green	green	green
Suitable for:	FEM 2a/b; 3a/b	FEM 2a/b; 3a/b	FEM 2a/b; 3a/b